# Opal Flash

## Optimizing your comfort

- Low profile
- Simple maintenance
- Easy installation
- Silent partner

Ozone Friendly
R407 C

| Model | | CAMG-18H | CAMG-24H | CAMG-363H | CAMG-483H |
|---|---|---|---|---|---|
| **Capacity** | | | | | |
| Cooling | Btu/h | 18,000 | 24,000 | 36,000 | 48,000 |
| | W | 5,270 | 7,027 | 10,541 | 14,055 |
| Heating | Btu/h | 20,500 | 28,000 | 40,000 | 53,000 |
| | W | 5,856 | 8,081 | 11,712 | 15,519 |
| Power Consumption Cooling | W | 2,050 | 3,100 | 5,000 | 5,400 |
| Power Consumption Heating | W | 2,150 | 2,950 | 5,700 | 6,000 |
| Operating Current (Cooling/Heating) | Amp 1Ph/3Ph | 9.8/10.5 | 13.8/13 | 8.6/9.7/10.1 | 9.0/10.1/10.8 |
| EER Cooling | Btu/W | 8.8 | 7.7 | 7.2 | 8.9 |
| COP Heating | W/W | 2.7 | 2.7 | 2.1 | 2.6 |
| Power Supply | V, Hz, Ph | 220~240,50,1 | 220~240,50,1 | 380, 50, 3 | 380, 50, 3 |
| **Indoor Unit** | | | | | |
| Dimensions (LxHxD) | mm | 580x580x254 | 840x840x240 | 840x840x310 | 840x840x310 |
| | mm | 650x650x30 | 950x950x40 | 950x950x40 | 950x950x40 |
| Airflow | $m^3/h$ | 860 | 1,050 | 1,600 | 1,750 |
| Noise Level | dB(A) | 43 | 43 | 47 | 47 |
| Net Weight Body/Panel | Kg | 21/3 | 36/6 | 40/6 | 40/6 |
| **Outdoor Unit** | | | | | |
| Dimensions (LxHxD) | mm | 845x695x335 | 895x860x330 | 990x965x360 | 940x1,245x360 |
| Noise Level | dB(A) | 56 | 60 | 65 | 65 |
| Refrigerant Lines - Drain | mm | 6.35 | 9.53 | 12.7 | 12.7 |
| Liquid/Gas Sides | mm | 12.7 | 15.9 | 19.0 | 19.9 |
| Net Weight | Kg | 53 | 79 | 101 | 110 |

Remarks: 1. Cooling capacities are based on indoor air temp. of 27°C DB, 19°C WB and outdoor air temp. of 35°C DB, 24°C WB.
2. The above specifications are subject to change without prior notice for product improvement purposes.

I feel | Intelligent defrosting | Sleep mode function | 175V Low voltage start up | Auto restart | Low noise level | Ionizer